

 **Install Method**

Cork Granules are mixed in a forced action mixer with the correct ratio of PU Binder and then poured into the area. The mix is then screeded and trowelled to the correct level. Requires a 16mm clean limestone base as a minimum.

 **Lead Time**

Immediately available from stock

 **Colour**

Natural Cork without colour additives

 **Ground Contours**

Flat/Slopes

 **Unit of Sale**

pm²

 **Product Description**

Exclusively provided by Playsmart, Corkeen is a cork based safety surface made from the outer layer of the cork oak tree. This renewable and natural material provides a safe and durable playground surface. With its flat and shock absorbent surface, Corkeen guarantees full accessibility for children of all abilities.

 **Size**

N/A

 **Application**

Education, Developer, Public Parks, Parish Councils, Commercial, Roof Tops

 **Maintenance**

Low

 **Guarantee**

5 years product, 2 years install



Size
N/A



Install Conditions
Dry, must be below 27 degrees and above 4 degrees



Fall Height Min.
1.45m @ 40mm depth



Ground Preparation
100mm clean stone



Material Type
"Natural cork granules are free of heavy metals, such as EDCs, T-VOCs, formaldehyde or PAHs"



Weight
Top available in 5.5kg bags and 5kg PU (90% ratio)



Guarantee
5 years product, 2 years install



Fall Height Max.
2.8m @ 130mm depth



Standards
Tested to BS EN 1177, Permeability EN 12616, BS7188, that includes abrasion, fire testing, slip resistance



Permeability



Environmental Data



Fire Rating