



Install Method

Ground stabilising mesh, mats tied together using 40 cable ties per m² including 6 per corner. Ties are cut off flush to the box, kit cut around using middle bridge, edges recessed into ground using plastic pegs, recess then reinstated and pegs covered and ground tampered.



Lead Time

Immediately available from stock



Colour

Black



Ground Contours

Can be installed on flat, mounds or slopes



Shock Pad

Yes, 30mm Smart Play Shock pad available to enable a CFH of 3m and prevent mats sinking.



Environmental Credentials

Average



Product Description

Superior fire retardant grass mat, FireSmart has become the industry standard for fire retardant surfacing and has established PlaySmart as the market leader in grass matting. Made from rubber, our mats provide a softer landing than safety tiles with a harsh plastic finish. With our trademarked installation specification, 10-year product and 5-year installation guarantees, by specifying FireSmart, you'll be choosing an environmentally friendly surfacing solution that is safe, durable and cost-effective.



Size

1m x 1.5m x 23mm



Application

Education, Developer, Public Parks, Parish Councils, Commercial



Maintenance

Low



Guarantee

10 years product, 5 years install



Unit of Sale

pm²/per mat



Size

1m x 1.5m x 23mm including a 10mm outer wall



Install Conditions

All weather



Fall Height With Shock Pad

3m



Ground Preparation

Good Grass Base, minimal groundworks



Material Type

Unique blend of recycled, reclaimed, and natural rubber makes this product a cost effective, environmentally friendly safety surface



Weight

13.5kg per



Fall Height Without Shock Pad

2m



Standards

Tested to BS EN 1177. Slip and fall resistant to British Standard BS 7188. Accredited to British Standard BS 7044. Self extinguish within 60 seconds of ignition



Permeability



Environmental Data



Fire Rating