



Install Method

Green Frog should be laid onto a tarmac, granno dust or a shock pad in order to give the best solution. Rolls should be laid out and then cut to size before glueing seams and fixing edges

Lead Time

Immediately available from stock

Colour

Green

Ground Contours

Flat and Slopes

Shock Pad

shock pad available up to 2.91CFH

Unit of Sale

pm²

Product Description

Green Frog Premium Artificial Grass made from Polyethylene and polypropylene. 35mm pile height. 16800 stitches m². Water permeable 60L/M²/H. UV stabilization 5000 H.

Size

2m x 25m or 4m x 25m rolls

Application

Education, Developer, Public Parks, Parish Councils, Commercial

Maintenance

Medium

Guarantee

8 years product, 2 years install



Size

2m x 25m or 4m x 25m rolls



Install Conditions

Dry



Fall Height Min.

0.6m (artificial grass onto tarmac/MOT & Granno Base)



Ground Preparation

100mm MOT Type One Base and 25mm Granno Dust Recommended or Tarmac



Material Type

U shaped yarn, Polyethylene and polypropylene



Weight

2.7kg per m2



Guarantee

8 years product, 2 years install



Fall Height Max.

2.91m @ 90mm depth shock pad



Standards

Tested to BS EN 1177 and EN 13501-1:2007+A12009 Fire classification and BS 4790:1987 Hot Metal Nut Method



Permeability



Environmental Data



Fire Rating