

 **Install Method**

Jungle Mulch is mixed in a forced action mixer with the correct ratio of PU Binder and then poured into the area. The mix is then screeded and trowelled/rolled to the correct level. Requires an MOT type one base as a minimum.

 **Lead Time**

Immediately available from stock

 **Colour**

Tuscan Red, Coconut Brown, Autumn Gold, Forest Green, Cypress Brown, Rustic Blend, Original Blend

 **Ground Contours**

Flat/Slopes/Mounds

 **CFH**

Additional depths available to provide CFHs of up to 3.0m

 **Environmental Credentials**

Average

 **Product Description**

Jungle Mulch has a unique, proven organic colouring process which ensures colour stays vibrant. The colour of cheaper alternatives erodes quickly and causes mulched areas to turn black with the carbon rubbing off onto skin and clothes when touched. Jungle Mulch utilises a graded shred, which looks more like natural bark, unlike other mulch manufacturers who use the cheaper by-product of the recycling process, an inferior chip and shred. The ratio of PU to Mulch ensures that breakdown of the material will not occur.

 **Size**

N/A

 **Application**

Education (Not early years), Developer, Public Parks, Parish Councils, Commercial

 **Maintenance**

Medium

 **Guarantee**

3 years product, 2 years install

 **Unit of Sale**

pm²



Size
N/A



Install Conditions
Dry, must be below 27 degrees and above 4 degrees



Fall Height Min.
1.3m @ 40mm depth



Ground Preparation
100mm MOT Type One Base Recommended or Tarmac



Material Type
surfacing is made from shredded recycled lorry tyres (SBR rubber).



Weight
18KG bags of Mulch and 3.6kg PU (20% ratio)



Guarantee
3 years product, 2 years install



Fall Height Max.
3.0m @ 140mm depth



Standards
Tested to BS EN 1177, BS EN 7188:1998 + A2 2009 Ease of Ignition



Permeability



Environmental Data



Fire Rating