

 **Install Method**

RubbaSmart Granules is mixed in a forced action mixer with the correct ratio of PU Binder and then poured into the area. The mix is then screeded and trowelled to the correct level. Requires an MOT type one base as a minimum.

 **Lead Time**

Immediately available from stock

 **Colour**

Any

 **Ground Contours**

Flat/Slopes/Mounds

 **CFH**

Additional depths available to provide CFHs of up to 3.0m

 **Product Description**

RubbaSmart Tested to BS EN 1177. No hidden Hazards, non toxic. High quality virgin rubber product, not made from SBR rubber, this product is a true colour solution and will turn black over time. Impact absorbing safety surface for playgrounds and play areas. Uses a polyurethane/rubber composite mixed on site and wet poured in place to give a durable, low maintenance play surface. Available in a wide range of colours, RubbaSmart is an ideal solution for simple and complex designs alike.

 **Size**

NA

 **Application**

Education, Developer, Public Parks, Parish Councils, Commercial

 **Maintenance**

Low

 **Guarantee**

5 years product, 3 years install

 **Unit of Sale**

pm²



Size
N/A



Install Conditions
Dry, must be below 27 degrees
and above 4 degrees



Fall Height Min.
1.2m @ 40mm depth



Ground Preparation
100mm MOT Type One Base
Recommended or Tarmac



Material Type
EPDM rubber crumb -
virgin rubber



Weight
Top available in 25kg bags and
4.5kg PU (18% ratio)



Guarantee
5 years product, 3 years install



Fall Height Max.
3.0m @ 140mm depth



Standards
Tested to BS EN 1177



Permeability



Environmental Data



Fire Rating