

 **Install Method**

SmartPave is mixed in a forced action mixer with the correct ratio of PU Binder and then poured into the area. The mix is then screeded and trowelled to the correct level. Requires an MOT type one base as a minimum.

 **Lead Time**

Immediately available from stock

 **Colour**

Red, Gold, Silver

 **Ground Contours**

Flat/Slopes/Mounds

 **CFH**

NA

 **Product Description**

We offer two variations of SmartPave, the most popular being a water permeable surfacing system using a blend of naturally decorative aggregates and recycled rubber granules from used tyres. The other variation is resin bound gravel. Both variations of SmartPave are suitable for pedestrian, bicycle and equestrian traffic on pathways and rural trails. Our resin bound gravel is also suitable for driveways. Due to the smooth surface, SmartPave meets accessibility requirements for wheelchair users, prams and buggies.

 **Size**

NA

 **Application**

Education (Not early years), Developer, Public Parks, Parish Councils, Commercial

 **Maintenance**

Good

 **Guarantee**

3 years product, 2 years install

 **Unit of Sale**

pm²

**Size**

N/A

**Install Conditions**

Dry, must be below 27 degrees and above 4 degrees

**Fall Height Min.**

NA

**Ground Preparation**

100mm MOT Type One Base Recommended or Tarmac

**Material Type**

surfacing is made from shredded recycled tyres (SBR rubber) and 2-5mm stone aggregate

**Weight**

25KG bags 3.25KG PU (ratio 13%)

**Guarantee**

3 years product, 2 years install

**Fall Height Max.**

NA

**Standards**

NA

**Permeability****Environmental Data****Fire Rating**