



👜 Install Method

Cork Granules are mixed in a forced action mixer with the correct ratio of PU Binder and then poured into the area. The mix is then screeded and trowelled to the correct level. Requires an 16mm clean limestone base as a minimum.

🕓 Lead Time

Immediately available from stock

Colour

Ground Contours

Shock Pad Additional depths available to provide Size

Application

Education, Developer, Public Parks, Parish Councils, Commercial, Roof Tops

🛞 Maintenance

Low

Guarantee

5 years product, 2 years install

Unit of Sale

Product Description

Exclusively provided by Playsmart, Corkeen is a cork based safety surface made from the outer layer of the cork oak tree. This renewable and natural material provides a safe and durable playground surface. With its flat and shock absorbent surface, Corkeen guarantees full accessibility for children of all abilities.







Size



Install Conditions Dry, must be below 27 degrees and above 4 degrees



Fall Height Min. 1.45m @ 40mm depth



Ground Preparation



Weight

Top available in 5.5kg bags and 5kg PU (90% ratio)



Guarantee 5 years product, 2 years install



Fall Height Max. 2.8m @ 130mm depth



Standards

Tested to BS EN 1177, Permeability EN 12616, BS7188, that includes abrasion, fire testing, slip resistance



Material Type

"Natural cork granules are free of heavy metals, such as EDCs, T-VOCs, formaldehyde or PAHs"