

 **Install Method**

Jungle Mulch is mixed in a forced action mixer with the correct ratio of PU Binder and then poured into the area. The mix is then screeded and trowelled/rolled to the correct level. Requires an MOT type one base as a minimum.

 **Lead Time**

Immediately available from stock

 **Size**

N/A

 **Colour**

Tuscan Red, Coconut Brown, Autumn Gold, Forest Green, Cypress Brown, Rustic Blend, Original Blend

 **Application**

Education (Not early years), Developer, Public Parks, Parish Councils, Commercial

 **Ground Contours**

Flat/Slopes/Mounds

 **Maintenance**

Medium

 **CFH**

Additional depths available to provide CFHs of up to 3.0m

 **Guarantee**

3 years product, 2 years install

 **Environmental Credentials**

Average

 **Unit of Sale**

pm²

 **Product Description**

JungleMulch has a unique, proven organic colouring process which ensures colour stays vibrant. The colour of cheaper alternatives erodes quickly and causes mulched areas to turn black with the carbon rubbing off onto skin and clothes when touched. Jungle Mulch utilises a graded shred, which looks more like natural bark, unlike other mulch manufacturers who use the cheaper by-product of the recycling process, an inferior chip and shred. The ratio of PU to Mulch ensures that breakdown of the material will not occur.

**Size**

N/A

**Install Conditions**

Dry, must be below 27 degrees and above 4 degrees

**Fall Height Min.**

1.3m @ 40mm depth

**Ground Preparation**

100mm MOT Type One Base Recommended or Tarmac

**Material Type**

surfacing is made from shredded recycled lorry tyres

**Weight**

18KG bags of Mulch and 3.6kg PU (20% ratio)

**Guarantee**

3 years product, 2 years install

**Fall Height Max.**

3.0m @ 140mm depth

**Standards**

Tested to BS EN 1177, BS EN 7188:1998 + A2 2009 Ease of Ignition