



Install Method

RubbaSmart Granules is mixed in a forced action mixer with the correct ratio of PU Binder and then poured into the area. The mix is then screeded and trowelled to the correct level. Requires an MOT type one base as a minimum.

Lead Time

Immediately available from stock

Size

NA

Colour

Any

Application

Education, Developer, Public Parks, Parish Councils, Commercial

Ground Contours

Flat/Slopes/Mounds

Maintenance

Low

CFH

Additional depths available to provide

Guarantee

5 years product, 3 years install

Product Description

RubbaSmart Tested to BS EN 1177. No hidden Hazards, non toxic. High quality virgin rubber product, not made from SBR rubber, this product is a true colour solution and will turn black over time. Impact absorbing safety surface for playgrounds and play areas. Uses a polyurethane/rubber composite mixed on site and wet poured in place to give a durable, low maintenance play surface. Available in a wide range of colours, RubbaSmart is an ideal solution for simple and complex designs alike.

Unit of Sale

pm²

**Size**

N/A

**Install Conditions**

Dry, must be below 27 degrees and above 4 degrees

**Fall Height Min.**

1.2m @ 40mm depth

**Ground Preparation**

100mm MOT Type One Base Recommended or Tarmac

**Material Type**

EPDM rubber crumb – virgin rubber

**Weight**

Top available in 25kg bags and 4.5kg PU (18% ratio)

**Guarantee**

5 years product, 3 years install

**Fall Height Max.**

3.0m @ 140mm depth

**Standards**

Tested to BS EN 1177