



Install Method

SmartPave is mixed in a forced action mixer with the correct ratio of PU Binder and then poured into the area. The mix is then screeded and trowelled to the correct level. Requires an MOT type one base as a minimum.



Lead Time

Immediately available from stock



Colour

Red, Gold, Silver



Ground Contours

Flat/Slopes/Mounds



CFH

NA



Product Description

We offer two variations of SmartPave, the most popular being a water permeable surfacing system using a blend of naturally decorative aggregates and recycled rubber granules from used tyres. The other variation is resin bound gravel. Both variations of SmartPave are suitable for pedestrian, bicycle and equestrian traffic on pathways and rural trails. Our resin bound gravel is also suitable for driveways. Due to the smooth surface, SmartPave meets accessibility requirements for wheelchair users, prams and buggies.



Size

NA



Application

Education (Not early years), Developer, Public Parks, Parish Councils, Commercial



Maintenance

Good



Guarantee

3 years product, 2 years install



Unit of Sale

pm²



Size

N/A



Install Conditions

Dry, must be below 27 degrees and above 4 degrees



Fall Height Min.

NA



Ground Preparation

100mm MOT Type One Base Recommended or Tarmac



Material Type

surfacing is made from shredded recycled tyres (SBR rubber) and 2-5mm stone aggregate



Weight

25KG bags 3.25KG PU (ratio 13%)



Guarantee

3 years product, 2 years install



Fall Height Max.

NA



Standards

NA